increased system flexibility. Features:

- · Double row terminal with up to 30 total positions
- 20 to 30 AWG discrete wire PVC or Teflon[®] cable
- · Single or double ended
- Applications: medical, vending, automation, office equipment, testing, networks, gaming, lighting and power supplies

For more Discrete Wire Solutions, please visit samtec.com/discretewire

<u>चाचाच</u>

UNITED STATES • NORTHERN CALIFORNIA • SOUTHERN CALIFORNIA • SOUTH AMERICA • UNITED KINGDOM • GERMANY • FRANCE • ITALY • NORDIC/BALTIC BENELUX • ISRAEL • INDIA • AUSTRALIA / NEW ZEALAND • SINGAPORE • JAPAN • SHANGHAI • SHENZHEN • TAIWAN • HONG KONG • KOREA SEPTEMBER 2014

Assembly

(9,14) 360

Cable: MRTD/MRTDT ENC

Tooling

Hand Tool:


- CAT-HT-174-2024-11 (20-24 AWG)
- CAT-HT-174-2630-11 (26-30 AWG)

Mini Applicators:

- CAT-MA-174-2024-XX-01 (20-24 AWG)
 - CAT-MA-174-2630-XX-01 (26-30 AWG)








Panel Mount Discrete Wire

Terminal Cable Assembly and Components The .100" (2.54 mm) pitch Mini Mate[®] panel mount discrete wire cable assembly (MRTD/MRTDT Series) is ideal for in-line connections required to pass through a panel. The terminal cable assembly accommodates a panel thickness of .0329" (0,84 mm) to .0897" (2,28 mm). It is designed to mate with Samtec's Mini Mate®

socket cable assemblies with individually shrouded contacts for reliability in harsh environments. The system is available as components (IPR1/T1M74 Series), or as complete single and double ended assemblies with a 3-inch assembled length minimum. Double ended assemblies feature a socket end for



æ

Components