

REVISION A


DO NOT SCALE FROM THIS PRINT

DESIGNED & DIMENSIONED IN INCHES[MILLIMETERS]






EXPLODED VIEW
NOT TO SCALE
(FOR CLARITY ONLY)



-EE: 50μ " EXTRA HEAVY GOLD CENTER CONTACT, 50μ " EXTRA HEAVY GOLD OUTER CONTACT



F:\DWG\MISC\MKTG\PRF01-J-C-EE-405-SD-MKT.SLDDRW

NOTES:

1. MATERIAL:

BODY, CONTACT: BERYLLIUM COPPER INSULATORS: PTFE.

2. FINISH:

BODY, CONTACT: 50µ" MIN. GOLD OVER 50µ" MIN. NICKEL PLATE.

3. PCI P/N: 3776.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES. TOLERANCES ARE: DECIMALS ANGLES

.XX: ±.01[0.3] 1 .XXX: ±.005[0.13] .XXXX: ±.0005[0.013] PROPRIETARY MODIE

THIS DOCUMENT CONTAINS CONTROL DITTOR THIS DOCUMENT CONTAINS CONTROL TO THE THIS DOCUMENT AND THE THIS DOCUMENT THE THIS DITTOR THI

DO NOT SCALE DRAWING

SHEET SCALE: 5:1



520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

DESCRIPTION:

SMA JACK DIRECT SOLDER FOR RG-405 SEMI-RIGID CABLE

PRF01-J-C-EE-405-SD

BY: CANDY W 4/2/2019 S


SHEET 1 OF 2

REVISION A

CABLE APPLICATION VIEWS


1 A. PRE-TIN CABLE OUTER JACKET TO DIMENSION SHOWN.

1B. TRIM CABLE JACKET & DIELECTRIC, THEN POINT CENTER CONDUCTOR AS SHOWN (DO NOT NICK CENTER CONDUCTOR).



IN-PROCESS VIEW 1

- 2A. INSERT CABLE INTO CONNECTOR UNTIL CENTER CONDUCTOR PLUGS IN AND CABLE SEATS IN CONNECTOR BORE.
- 2B. SOLDER CABLE JACKET TO BODY WHERE SHOWN APPLYING HEAT TO EXTENDED BODY TAIL.



PROPRIETARY INFORMATION AND ALL DESIGN,
MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS
AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SANTEC,
INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE
OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR

REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

samtec

520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

DO NOT SCALE DRAWING

SMA JACK DIRECT SOLDER FOR RG-405 SEMI-RIGID CABLE

SHEET SCALE: 5:1

PRF01-J-C-EE-405-SD

BY: CANDY W 4/2/2019

SHEET 2 OF 2

IN-PROCESS VIEW 2

F:\DWG\MISC\MKTG\PRF01-J-C-EE-405-SD-MKT.SLDDRW