

NOTES:

1. MATERIAL:

BODY, COUPLING & CLAMP NUTS: STAINLESS STEEL.
CONTACT & LOCK RING: BERYLLIUM COPPER.
SOLDER FERRULE: BRASS.
GASKET & O-RING: SILICONE RUBBER.
INSULATORS: PTFE.

DIELECTRIC BEADS: ULTEM 1000.

2. FINISH:

BODY, COUPLING & CLAMP NUTS: PASSIVATED. CONTACT: 50µ" MIN. GOLD OVER 50µ" MIN. NICKEL PLATE. SOLDER FERRULE: 10µ" MIN. GOLD OVER 50µ" MIN. NICKEL PLATE.

3. DELETED NOTE.

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, U.S., PATENT RIGHTS AND SALES RIGHTS ARE DAVIESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE ESCLOSED, IN WHOSE OF PART, TO ANY UNAUTHORIZED PESSON OR ENTITY NOR PREPRODUCED. TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSPICT OF SAMTE. INC.

SHEET SCALE: 2:1
DO NOT SCALE DRAWING




520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

DESCRIPTION: SMA RA PLUG, SOLDER CLAMP FOR HARBOUR LL335I CABLE

PRF01-P-C-EP-335A-RS


BY: HENSON T 07/30/2020 SHEET 1 OF 3

CABLE APPLICATION VIEWS




1. TRIM CABLE TO EXPOSE BRAIDS AND DIELECTRIC AS SHOWN.

IN-PROCESS 1



- 2A. INSERT CABLE INTO SOLDER FERRULE UNTIL BRAIDS SEAT IN FERRULE. THEN SOLDER BOTH CABLE BRAIDS WHERE SHOWN.
- 2B. TRIM CABLE DIELECTRIC FLUSH WITH FACE OF FERRULE.

IN-PROCESS 2



- 3A. SLIDE DIELECTRIC STOP (ϕ .315[8.00] OD) ONTO CABLE CENTER CONDUCTOR AGAINST FACE OF SOLDER FERRULE.
- 3B. SOLDER CONTACT FLUSH TO DIELECTRIC STOP TO DIMENSION SHOWN.



520 PARK EAST BLVD, NEW ALBANY, IN 47150

PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

DO NOT SCALE DRAWING


SHEET SCALE: 1.5:1

DESCRIPTION: SMA RA PLUG, SOLDER CLAMP FOR HARBOUR LL335I CABLE


PRF01-P-C-EP-335A-RS 07/30/2020 SHEET 2 OF 3 BY: HENSON T

IN-PROCESS 3

F:\DWG\MISC\MKTG\PRF01-P-C-EP-335A-RS-MKT.SLDDRW



IN-PROCESS 4



5. INSERT CABLE/CONTACT SUB-ASSEMBLY INTO CONNECTOR UNTIL SEATED AND TIGHTEN CLAMP NUT TO 35-45 IN-LBS.

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, PROPRIETARY INFORMATION AND ALL DESIGN, AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DECICIOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERBED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANARER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

DESCRIPTION: 6. AND AD ADMINISTRATION OF SAME CONTROL OF

DO NOT SCALE DRAWING

SHEET SCALE: 1.5:1

SMA RA PLUG, SOLDER CLAMP FOR HARBOUR LL335I CABLE

PRF01-P-C-EP-335A-RS

BY: HENSON T 03

07/30/2020 SHEET 3 OF 3

IN-PROCESS 5

F:\DWG\MISC\MKTG\PRF01-P-C-EP-335A-RS-MKT.SLDDRW