




Project Number: Design Qualification Test Report		Tracking Code: 183062_Report_Rev_3		
Requested by: Mark Shireman		Date: 3/14/2013	Product Rev: N/A	
Part #: MEC1-170-02-L-D-RA1-SL \ Edge card		Lot #: N/A	Tech: Tony Wagoner	Eng: Eric Mings
Part description: MEC1-RA				Qty to test: 9
Test Start: 03/14/2012	Test Completed: 03/15/2012			



DESIGN QUALIFICATION TEST REPORT

**MEC1-170-02-S-D-RA1-SL
Edge Card**

CERTIFICATION

All instruments and measuring equipment were calibrated to National Institute for Standards and Technology (NIST) traceable standards according to ISO 10012-1 and ANSI/NCSL 2540-1, as applicable.

All contents contained herein are the property of Samtec. No portion of this report, in part or in full shall be reproduced without prior written approval of Samtec.

SCOPE


To perform the following tests: Design Qualification test. Please see test plan.

APPLICABLE DOCUMENTS

Standards: EIA Publication 364

TEST SAMPLES AND PREPARATION

- 1) All materials were manufactured in accordance with the applicable product specification.
- 2) All test samples were identified and encoded to maintain traceability throughout the test sequences.
- 3) Either an automated cleaning procedure or an ultrasonic cleaning procedure may be used.
- 4) The automated procedure is used with aqueous compatible soldering materials.
- 5) Any additional preparation will be noted in the individual test sequences.
- 6) Solder Information: Lead Free
- 7) Re-Flow Time/Temp: See accompanying profile.

TYPICAL OVEN PROFILE (Soldering Parts to Test Boards)

FLOWCHARTS**Current Carrying Capacity - Double Row**

TEST STEP	GROUP B1 3 Mated Assemblies 2 Contacts Powered	GROUP B2 3 Mated Assemblies 4 Contacts Powered	GROUP B3 3 Mated Assemblies 6 Contacts Powered	GROUP B4 3 Mated Assemblies 8 Contacts Powered	GROUP B5 3 Mated Assemblies All Contacts Powered
01	CCC	CCC	CCC	CCC	CCC

(TIN PLATING) - Tabulate calculated current at RT, 65°C, 75°C and 95°C
after derating 20% and based on 105°C

(GOLD PLATING) - Tabulate calculated current at RT, 85°C, 95°C and 115°C
after derating 20% and based on 125°C

CCC, Temp rise = EIA-364-70

ATTRIBUTE DEFINITIONS

The following is a brief, simplified description of attributes.

TEMPERATURE RISE (Current Carrying Capacity, CCC):

- 1) EIA-364-70, *Temperature Rise versus Current Test Procedure for Electrical Connectors and Sockets*.
- 2) When current passes through a contact, the temperature of the contact increases as a result of I^2R (resistive) heating.
- 3) The number of contacts being investigated plays a significant part in power dissipation and therefore temperature rise.
- 4) The size of the temperature probe can affect the measured temperature.
- 5) Copper traces on PC boards will contribute to temperature rise:
 - a. Self heating (resistive)
 - b. Reduction in heat sink capacity affecting the heated contacts
- 6) A de-rating curve, usually 20%, is calculated.
- 7) Calculated de-rated currents at three temperature points are reported:
 - a. Ambient
 - b. 80° C
 - c. 95° C
 - d. 115° C
- 8) Typically, neighboring contacts (in close proximity to maximize heat build up) are energized.
- 9) The thermocouple (or temperature measuring probe) will be positioned at a location to sense the maximum temperature in the vicinity of the heat generation area.
- 10) A computer program, *TR 803.exe*, ensures accurate stability for data acquisition.
- 11) Hook-up wire cross section is larger than the cross section of any connector leads/PC board traces, jumpers, etc.
- 12) Hook-up wire length is longer than the minimum specified in the referencing standard.

RESULTS


Temperature Rise, CCC at a 20% de-rating

- CCC for a 30°C Temperature Rise -----1.6A per contact with 2 adjacent contacts powered
- CCC for a 30°C Temperature Rise -----1.2A per contact with 4 adjacent contacts powered
- CCC for a 30°C Temperature Rise -----1.0A per contact with 6 adjacent contacts powered
- CCC for a 30°C Temperature Rise -----0.9A per contact with 8 adjacent contacts powered
- CCC for a 30°C Temperature Rise -----0.4A per contact with all adjacent contacts powered

DATA SUMMARIES

TEMPERATURE RISE (Current Carrying Capacity, CCC):


- 1) High quality thermocouples whose temperature slopes track one another were used for temperature monitoring.
- 2) The thermocouples were placed at a location to sense the maximum temperature generated during testing.
- 3) Temperature readings recorded are those for which three successive readings, 15 minutes apart, differ less than 1° C (computer controlled data acquisition).
- 4) Adjacent contacts were powered:
 - a. Linear configuration with all adjacent conductors/contacts powered



DATA SUMMARIES Continued


b. Linear configuration with 4 adjacent conductors/contacts powered

183062
 4 (2X2) Contacts Powered in Series
 Part Numbers: ASP-151884-03/Edge Card
 Current Rating per Contact (30 Deg. Rise, 20% Derated) = 1.2 Amps



DATA SUMMARIES Continued


c. Linear configuration with 6 adjacent conductors/contacts powered



DATA SUMMARIES Continued


d. Linear configuration with 8 adjacent conductors/contacts powered

183062
 8 (2X4) Contacts Powered in Series
 Part Numbers: ASP-151884-03/Edge Card
 Current Rating per Contact (30 Deg. Rise, 20% Derated) = 0.9 Amps



DATA SUMMARIES Continued

e. Linear configuration with all adjacent conductors/contacts powered



EQUIPMENT AND CALIBRATION SCHEDULES**Equipment #:** MO-04**Description:** Multimeter /Data Acquisition System**Manufacturer:** Keithley**Model:** 2700**Serial #:** 0798688**Accuracy:** See Manual

... Last Cal: 04/30/2011, Next Cal: 04/30/2012

Equipment #: PS-07**Description:** Power Supply**Manufacturer:** Agilent**Model:** AT-6031A**Serial #:** 2721A00648**Accuracy:** See Manual See Manual

... Last Cal: 08/21/2011, Next Cal: 08/21/2012