

Series: QMS-RA/QFS-RA

Description: Board-to-Board, 0.635mm Pitch, Right Angle to Right Angle

Frequency Domain Data Summary

Table 1 - Single-Ended Connector System Performance			
Case 1 = Short Row; Case 2 = Long Row			
Case	Test Parameter	Configuration	
1	Insertion Loss	GSG	3dB@ 14.5 GHz
	Return Loss	GSG	>10dB to 5.9 GHz
	Near-End Crosstalk	GAQG	<-20dB to 0.4 GHz
		GAGQG	<-20dB to 9.4 GHz
		Xrow, GAG to GQG	<-20dB to 20 GHz
	Far-End Crosstalk	GAQG	<-20dB to 7 GHz
		GAGQG	<-20dB to 13.8 GHz
Xrow, GAG to GQG		<-20dB to 20 GHz	
2	Insertion Loss	GSG	3dB@ 20 GHz
	Return Loss	GSG	>10dB to 4 GHz
	Near-End Crosstalk	GAQG	<-20dB to 0.3 GHz
		GAGQG	<-20dB to 20.0 GHz
	Far-End Crosstalk	GAQG	<-20dB to 4.5 GHz
		GAGQG	<-20dB to 6.9 GHz

Table 2 - Differential Connector System Performance			
Case 1 = Short Row; Case 2 = Long Row			
Case	Test Parameter	Configuration	
1	Insertion Loss	GSSG	3dB@ 7 GHz
	Return Loss	GSSG	>10dB to 1.2 GHz
	Near-End Crosstalk	GAAQQG	<-20dB to 2 GHz
		GAAGQQG	<-20dB to 20 GHz
		Xrow, GAAG to GQQG	<-20dB to 20 GHz
	Far-End Crosstalk	GAAQQG	<-20dB to 20 GHz
		GAAGQQG	<-20dB to 20 GHz
Xrow, GAAG to GQQG		<-20dB to 20 GHz	
2	Insertion Loss	GSSG	3dB@ 4.7 GHz
	Return Loss	GSSG	>10dB to 0.8 GHz
	Near-End Crosstalk	GAAQQG	<-20dB to 1.5 GHz
		GAAGQQG	<-20dB to 20 GHz
	Far-End Crosstalk	GAAQQG	<-20dB to 7.4 GHz
		GAAGQQG	<-20dB to 20 GHz

Series: QMS-RA/QFS-RA

Description: Board-to-Board, 0.635mm Pitch, Right Angle to Right Angle

Bandwidth Chart – Single-Ended & Differential Insertion Loss

Case 1 = Short Row; Case 2 = Long Row

QFS-RA/QMS-RA Connector Series

