

Series: QTH/QSH

Description: High Speed Ground Plane Header, 0.5mm (.0197") Pitch, 16mm (.630") Stack Height

Frequency Domain Data Summary

Table 1 - Single-Ended Connector System Performance		
Test Parameter	Configuration	
Insertion Loss	GSG	3dB @ 5.138 GHz
Return Loss	GSG	>10dB to 2.338 GHz
Near-End Crosstalk	GAQG	< -20dB to 0.325 GHz
	GAGQG	< -20dB to 5.038 GHz
	Xrow, GAG to GQG	< -20dB to 20 GHz
Far-End Crosstalk	GAQG	< -20dB to 6.65 GHz
	GAGQG	< -20dB to 5.213 GHz
	Xrow, GAG to GQG	< -20dB to 20 GHz

Table 2 - Differential Connector System Performance		
Test Parameter	Configuration	
Insertion Loss	GSSG	3dB @ 5.825 GHz
Return Loss	GSSG	>10dB to 0.85 GHz
Near-End Crosstalk	GAAQQG	< -20dB to 1.35 GHz
	GAAGQQG	< -20dB to 20 GHz
	Xrow, GAAG to GQQG	< -20dB to 20 GHz
Far-End Crosstalk	GAAQQG	< -20dB to 20 GHz
	GAAGQQG	< -20dB to 20 GHz
	Xrow, GAAG to GQQG	< -20dB to 20 GHz

Series: QTH/QSH

Description: High Speed Ground Plane Header, 0.5mm (.0197") Pitch, 16mm (.630") Stack Height

Bandwidth Chart – Single-Ended & Differential Insertion Loss

QTH/QSH Ground Plane Header Series

